



# Innocrush 35

## IMPACT CRUSHER

<b>Transport dimensions</b>	<b>Total</b>
Length	<b>11.620 mm</b>
Width	<b>2.550 mm</b>
Height	<b>3.220 mm</b>
Gross weight	<b>35,5 t</b>
<b>Impact Crusher</b>	<b>Model - 204 L</b>
Inlet opening	<b>1.250 x 705 mm</b>
Throughput capacity	<b>350 t/h</b>
Rotor	<b>1010 mm</b>
Equipment	<b>4 blow bars</b>
Swing beams	<b>2 independent</b>
Approach swing beams	<b>Hydraulic</b>
<b>Hopper</b>	
Volume	<b>4 m<sup>3</sup></b>
Length	<b>3.340 mm</b>
Width	<b>2.340 mm</b>
<b>Vibrating feeder</b>	
Feeder length	<b>3.370 mm</b>
Width	<b>1.240 mm</b>
Length pre-screen	<b>920 mm</b>
Gap width	<b>40 - 60 mm</b>
<b>Main belt</b>	
Width	<b>1.200 mm</b>
Discharge height	<b>3.000 mm</b>
Head of conveyor foldable	<b>Hydraulic</b>
<b>Side belt</b>	
Width	<b>650 mm</b>
Discharge height	<b>2.770 mm</b>
Conveyor foldable	<b>Hydraulic</b>
<b>Tracks</b>	
Pad width	<b>400 mm</b>
2 selectable speed	<b>1,5 km/h - 3 km/h</b>
<b>Engine</b>	
Caterpillar	<b>C11 - 287 kw a 2.200 rpm</b>
<b>Magnetic metal separator</b>	<b>Permanent</b>
Width	<b>750 mm</b>
<b>Remote Control</b>	<b>Standard</b>
Wireless	<b>12 channels</b>