



Innocrush 50

IMPACT CRUSHER

Transport dimensions	Total
Length	13.420 mm
Width	2.980 mm
Height	3.600 mm
Gross weight	49,8 t
Impact Crusher	Model - 204
Inlet opening	1.260 x 1.060 mm
Throughput capacity	450 t/h
Rotor	1300 mm
Equipment	4 blow bars
Swing beams	2 independent
Approach swing beams	Hydraulic
Hopper	
Volume	6,5 m ³
Length	3.670 mm
Width	2.690 mm
Vibrating feeder and 2 - deck - screen (Grizzly)	
Length : Feeder / 2 deck screen (Grizzly)	3.310mm / 1.800 mm
Width	1.240 mm
Size of mesh lower deck	selectable
Gap width	40 - 60 mm
Main belt	
Width	1.200 mm
Discharge height	3.475 mm
Head of conveyor foldable	Hydraulic
Side belt	
Width	800 mm
Discharge height	2.790 mm
Conveyor foldable	Hydraulic
Tracks	
Pad width	500 mm
2 selectable speed	1,5 km/h - 3 km/h
Engine	
Standard - Caterpillar	C11 - 287 kw a 2.200 rpm
Optional - Caterpillar	C13 - 328 kw a 2.200 rpm
Magnetic metal separator	Standard
Width	750 mm
Remote Control	
Wireless	12 channels