



Innocrush 75

IMPACT CRUSHER

Transport dimensions	Total
Length	16.500 mm
Width	3.285 mm
Height	3.830 mm
Gross weight	72,5 t
Impact Crusher	Model - 205
Inlet opening	1.560 x 1.060 mm
Throughput capacity	600 t/h
Rotor	1300 mm
Equipment	4 barras
Swing beams	2 independent
Approach swing beams	Hydraulic
Hopper	
Volume	8 m ³
Length	4.400 mm
Width	2.840 mm
Vibrating feeder and 2 - deck - screen (Grizzly)	
Length : Feeder / 2 deck screen (Grizzly)	3.610 mm / 2.275 mm
Width	1.510 mm
Size of mesh lower deck	selectable
Gap width	40 - 120 mm
Main belt	
Width	1.200 mm
Discharge height	4.175 mm
Head of conveyor foldable	Hydraulic
Side belt	
Width	1.000 mm
Discharge height	2.367 mm
Conveyor foldable	Hydraulic
Tracks	
Pad width	600 mm
2 selectable speed	1,5 km/h - 3 km/h
Engine	
Standard - Caterpillar	C15 - 403 kw a 2.200 rpm
Magnetic metal separator	Permanent
Width	900 mm
Remote Control	Standard
Wireless	12 channels